



Design Project 1

Delphine Damiens, Arina Pavlova, Alec De Trogoff




Table Of Contents

Design Idea	
Climate & Site Analysis	
Conclusions & Strategies	
References	
Design Process & Iterations	
Fabrication, Programmatic Diagrams & Materials	
Diagrams & Simulations	
Orthographic Drawings	
Final Project Installation	




DESIGN IDEA











CLIMATE & SITE ANALYSIS






GLOBAL HORIZONTAL RADIATION
















Summer Solstice





Autumnal Equinox




CONCLUSIONS & STRATEGIES









APPARATUS




REFERENCES





Hexacoralla. — Sechsstrahlige Sternkorallen.



Ernst Haeckel





Rogan Brown Paper Sculptures



'Cloaca' by Wim Delvoye





'HORTUS.PARIS' Ecologic Studio, 2013




'Hylozoic Ground' , Philip Beesley




DESIGN PROCESS & ITERATIONS































FABRICATION, PROGRAMMATIC DIAGRAMS & MATERIALS














TOP PIECE:
DAYLIGHT SENSOR



Equivalence of measurments to sound produced




Evolution of the measured information is linear to the evolution of the produced frequencies, i.e a double in the relative humidity will produce a sound twice as high as it was, and similarly for the evolution of solar radiation.

For relative humidity, a measure of 75% humidity would produce a frequency of 1072 Hz, and a measure of 80% humidity a frequency of 1500 Hz.

For solar radiation, a measure of 0 Wh/m² would produce a frequency of 300 Hz, and a measure of 955.5 Hz.

Coding diagram




Arduino Uno


DP1.ino

```
1 #include <DHT.h>
2
3 // Define the pin connections
4 #define DHTPIN 2 // Digital pin for the Temperature & Humidity Sensor
5 #define DHTTYPE DHT11 // DHT 11 sensor type
6 #define LIGHT_SENSOR_PIN A0 // Analog pin for the Light Sensor
7 #define BUZZER1_PIN 3 // Digital pin for the first Grove Buzzer
8 #define BUZZER2_PIN 4 // Digital pin for the second Grove Buzzer
9
10 DHT dht(DHTPIN, DHTTYPE);
11
12 void setup() {
13   pinMode(BUZZER1_PIN, OUTPUT);
14   pinMode(BUZZER2_PIN, OUTPUT);
15   Serial.begin(9600);
16   dht.begin();
17 }
18
19 void loop() {
20   // Read humidity
21   float humidity = dht.readHumidity();
22   if (isnan(humidity)) {
23     Serial.println("Failed to read from DHT sensor!");
24     return;
25   }
26
27   // Read light intensity
28   int lightIntensity = analogRead(LIGHT_SENSOR_PIN);
29
30   // Map the readings to PWM duty cycles (sound intensity)
31   int humidityPWM = map(humidity, 20, 90, 50, 255); // Adjust range as per expected humidity levels
32   int lightPWM = map(lightIntensity, 0, 1023, 50, 255);
33
34   // Ensure PWM is within a valid range
35   humidityPWM = constrain(humidityPWM, 0, 255);
36   lightPWM = constrain(lightPWM, 0, 255);
37
38   // Activate the buzzers based on the mapped values
```

Output




DIAGRAMS AND SIMULATIONS




ORIENTATION OF APPARATUS

Optimal time for the use of the apparatus is approximately 12 pm.



Sunlight should not be measured after 3 pm because of the orientation of the sensors.



INCIDENT RADIATION SIMULATION





View from North



View from East

ORTHOGRAPHIC DRAWINGS






2029.07

580.56



1534.16



1087.10

1073.12

2030.42







FINAL PROJECT INSTALLATION









